

HEDRION deli

Highly efficient, interchangeable LED glass reflector lamps and 120° light modules for professional lighting solutions in bakeries and meat shops.

HEDRION deli 25W

* High-quality dichroic glass reflectors (12°/25°/40°)

* Very long service life (50 000 h)

* Especially for the illumination of bread/baked goods (2500K)

respectively meat/sausage products (2000K)

* For use in BLV HEDRION luminaires

with 30W max. output power

* Dimmable

Article no.	Designation	Base	Ø [mm]	Length [mm]	Burning position	Lamp voltage [V]	Lamp current [mA]	Nominal lamp power @700mA [W]	Rated lamp power @700mA [W]	Beam angle [°]	Nominal luminous flux @700mA [lm]	Rated useful luminous flux at 90° @700mA [lm]	Rated useful luminous flux at 120° @700mA [lm]	Rated peak intensity @700mA [cd]	Colour temperature [K]	Colour temperature [descr.]	Colour rendering index Ra	Colour consistency	Nominal service life [h]	Lamp lumen maintenance at the end of the nominal service life [%]	Number of switching cycles before premature failure	Starting time [s]	Warm-up time to 60% luminous flux [s]	Weighted energy consumption @700mA [kWh/r 000 h]	Energy efficiency class @700mA
HEO25720012	25W, 2000K, 12°	G46d	60,0	70,0	u360	36,0	350-700	25	25,3	12	2 250	2 040		16 020	2 000	pink white	n.a.	3 SDCM	50 000	70	unlimited	< 0,2s	≤ 1s	28	A+
HEO25720025	25W, 2000K, 25°	G46d	60,0	70,0	u360	36,0	350-700	25	25,3	25	2 250	2 200		7 410	2 000	pink white	n.a.	3 SDCM	50 000	70	unlimited	< 0,2s	≤ 1s	28	A+
HEO25720040	25W, 2000K, 40°	G46d	60,0	70,0	u360	36,0	350-700	25	25,3	40	2 250	2 210		4 980	2 000	pink white	n.a.	3 SDCM	50 000	70	unlimited	< 0,2s	≤ 1s	28	A+
HEO25720120	25W, 2000K, 120°	G46d	60,0	28,5	u360	36,0	350-700	25	25,3	120	2 250		1 950	840	2 000	pink white	n.a.	3 SDCM	50 000	70	unlimited	< 0,2s	≤ 1s	28	A+
HEO25825012	25W, 2500K, 12°	G46d	60,0	70,0	u360	36,0	350-700	25	25,3	12	2 420	2 200		17 230	2 500	warm white	n.a.	3 SDCM	50 000	70	unlimited	< 0,2s	≤ 1s	28	A+
HEO25825025	25W, 2500K, 25°	G46d	60,0	70,0	u360	36,0	350-700	25	25,3	25	2 420	2 360		7 970	2 500	warm white	n.a.	3 SDCM	50 000	70	unlimited	< 0,2s	≤ 1s	28	A+
HEO25825040	25W, 2500K, 40°	G46d	60,0	70,0	u360	36,0	350-700	25	25,3	40	2 420	2 380		5 360	2 500	warm white	n.a.	3 SDCM	50 000	70	unlimited	< 0,2s	≤ 1s	28	A+
HEO25825120	25W, 2500K, 120°	G46d	60,0	28,5	u360	36,0	350-700	25	25,3	120	2 420		2 100	910	2 500	warm white	n.a.	3 SDCM	50 000	70	unlimited	< 0,2s	≤ 1s	28	A+