

AMALION LED WW wallwasher surface-mounted luminaires

Linear LED surface-mounted luminaires for the photosynthetically effective illumination of vertical green areas



Version 200304

AMALION LED wallwasher luminaires for ceiling or suspended mounting

* LED module housing made of aluminium, silver anodised
* Plastic end caps, black

* Neutral white CCT
* Excellent colour rendering

* Spectral distribution optimised for indoor greening
* Uniform exposure of vertical surfaces (Wallwasher WW)

Article no.	Designation	Nominal system wattage [W]	Radiation characteristics	Luminous flux [lm]	PPF [$\mu\text{mol/s}$]	CCT [K]	CRI	Outer dimensions L x B x H [mm]	Ceiling cut-out L x B [mm]	Minimum installation depth [mm]	Weight [kg]	IP class / IK class	Dimmable
109772	AMALION 120 L+D L1s SW P1 WW	120	WW (asym.)	8 600	136	4 000	95	390 x 205 x 130	n.a.	n.a.	6.0	IP44 / IK06	no
109773	AMALION 120 L+D L1s DA P1 WW	120	WW (asym.)	8 600	136	4 000	95	390 x 205 x 130	n.a.	n.a.	6.0	IP44 / IK06	DALI
109774	AMALION 240 L+D L2s SW P1 WW	240	WW (asym.)	17 200	272	4 000	95	610 x 205 x 130	n.a.	n.a.	11.0	IP44 / IK06	no
109775	AMALION 240 L+D L2s DA P1 WW	240	WW (asym.)	17 200	272	4 000	95	610 x 205 x 130	n.a.	n.a.	11.0	IP44 / IK06	DALI
109776	AMALION 360 L+D L3 SW P1 WW	360	WW (asym.)	25 800	408	4 000	95	870 x 205 x 130	n.a.	n.a.	15.5	IP44 / IK06	no
109777	AMALION 360 L+D L3 DA P1 WW	360	WW (asym.)	25 800	408	4 000	95	870 x 205 x 130	n.a.	n.a.	15.5	IP44 / IK06	DALI

Accessories

* Accessories for mounting and electrical connection of wallwasher surface-mounted luminaires

Article no.	Designation	
109791	TL-CEIL-FIX30 SHORT	Fixed 30° mounting bracket for ceiling mounting
109793	TL-CEIL-ADJ-SHORT	Adjustable mounting bracket for ceiling mounting
112404	TL-SUSP-FIX30	Fixed 30° mounting bracket for suspended mounting (set consists of left and right bracket); for combination with TL-SUSP-CORD
109789	TL-SUSP-CORD	2 m steel cord with suspension loop at one end and adjustable hook at the other end; for combination with TL-SUSP-HOOK (set includes 4 pcs. for one luminaire)
108216	RST16i5 SUPCBL 0.5M	0.5 m connection cable with connector female at one end and free cable ends at the other end
106410	RST16i5 FCON tb	Connector, 5 pole, female, for assembling customised supply cables