

Halogen floodlight lamps

Double-ended, mains-voltage halogen lamps for various indoor and outdoor uses.



Version 200806

Halogen floodlight lamps ! Discontinued product - available as long as supplies last !

* For operation on mains voltage without transformer

* High luminous flux constancy for the entire service life

* Dimmable

Article no.	Model	Designation	Base	Ø [mm]	Length [mm]	Burning position	Lamp voltage [V]	Nominal lamp power [W]	Rated lamp power [W]	Nominal luminous flux [lm]	Rated luminous flux [lm]	Colour temperature [K]	Colour temperature [descr.]	Colour rendering index Ra	Nominal service life [h]	Rated service life for a lamp survival rate of 50 % [h]	Number of switching cycles before premature failure	Starting time [s]	Warm-up time to 60 % luminous flux [s]	Weighted energy consumption [kWh / 1 000 h]	Energy efficiency class
102982	11110101	750W 240V R7s H	R7s	12,0	185,7	p15	240	750	750,0	15 000	15 000	2 950	warm white	100	2 000	2 000	10 000	< 0,2s	≤ 1s	795	D
102928	10020101	1500W 240V R7s H	R7s	12,0	250,7	p15	240	1500	1500,0	33 000	33 000	3 000	warm white	100	2 000	2 000	10 000	< 0,2s	≤ 1s	1 590	D
102984	11140101	2000W 240V R7s H	R7s	12,0	327,4	p15	240	2000	2000,0	44 000	44 000	3 000	warm white	100	2 000	2 000	10 000	< 0,2s	≤ 1s	2 120	D