

STATURION LED astro floodlights

For energy-efficient lighting of smaller sports facilities, indoor and outdoor



Version 191017

STATURION LED astro

* Body from die-cast aluminium, powder coated
* Tempered protection glass

* Adjustable mounting bracket
* Various light distributions

* TM: Suspended mounting on traverses
* PM: Pole mounting upright

* High ingress protection and impact resistance
* Virtually flicker-free

Article no.	Designation	Number of LEDs	System wattage [W]	Beam angle [°]	Luminous flux [lm] @ Ta 25°	Colour temperature [K]	Colour rendering index Ra	Flicker Factor FF [%]	Dimensions w/o bracket Ø x H [mm]	Windage area [m²]	Weight [kg]	Housing colour	IP class / impact resistance
111496	STATURION LED astro 1785-100 TM	12	101	sym. 60°	11 068	4 000	70	4%	462 x 100	0.055 - 0.172	12.3	silver-grey	IP66 / IK08
111497	STATURION LED astro 1785-250 TM	32	235	sym. 60°	26 357	4 000	70	< 1%	512 x 100	0.061 - 0.210	14.0	silver-grey	IP66 / IK08
111498	STATURION LED astro 1785-400 TM	28	381	sym. 60°	37 259	4 000	70	8%	512 x 184	0.085 - 0.210	17.2	silver-grey	IP66 / IK08
111499	STATURION LED astro 1794-250 PM	32	270	asym. 30°	24 203	4 000	70	< 1%	512 x 100	0.050 - 0.223	15.1	silver-grey	IP66 / IK08
111500	STATURION LED astro 1794-400 PM	28	395	asym. 30°	29 493	4 000	70	8%	512 x 184	0.081 - 0.223	18.1	silver-grey	IP66 / IK08
103851	STATURION LED astro 1787-250 TM	32	235	asym. 50°	24 717	4 000	70	< 1%	512 x 100	0.061 - 0.210	14.0	silver-grey	IP66 / IK08
111501	STATURION LED astro 1787-400 TM	28	378	asym. 50°	36 000	4 000	70	8%	512 x 184	0.085 - 0.210	17.2	silver-grey	IP66 / IK08

Further models on request

Accessories

* Safety guard for screw mounting

Article no.	Designation	Weight [kg]
111502	SAFETY GUARD astro 12	0.23
111503	SAFETY GUARD astro 28-36	0.69