

# STATURION LED forum floodlights

For energy-efficient lighting of training fields, sports facilities, stadiums or industrial areas

Version 191206

## STATURION LED forum

\* Body from die-cast aluminium, powder coated  
\* Modular design with 1, 2 or 3 LED modules

\* Adjustable mounting bracket  
\* Tempered protection glass

\* High ingress protection and impact resistance  
\* Virtually flicker-free

\* For EN 12193 compliant lighting of sports facilities

Article no.	Designation	No. of LED modules	LED current [mA]	System wattage [W]	Beam angle [°]	Luminous flux [lm] @ Ta 25°	Colour temperature [K]	Colour rendering index Ra	Flicker Factor FF [%]	Dimensions with bracket W x D x H [mm]	Windage area [m²]	Weight [kg]	Housing colour	IP class / Impact resistance
111504	STATURION LED forum 2187-400	1	1 050	396	17° sym.	37 087	4 000	70	~ 8%	642 x 228 x 281	0.028 - 0.133	9.0	graphite-grey	IP66 / IK08
111505	STATURION LED forum 2180-450	1	1 200	462	30° sym.	47 954	4 000	70	~ 8%	642 x 228 x 281	0.028 - 0.133	9.0	graphite-grey	IP66 / IK08
111506	STATURION LED forum 2183-250	1	700	257	120° sym.	36 300	4 000	70	~ 8%	642 x 228 x 281	0.028 - 0.133	9.0	graphite-grey	IP66 / IK08
111507	STATURION LED forum 2183-400	1	1 050	396	120° sym.	32 350	4 000	70	~ 8%	642 x 228 x 281	0.028 - 0.133	9.0	graphite-grey	IP66 / IK08
111508	STATURION LED forum 2185-400	1	1 050	396	50° asym.	39 606	4 000	70	~ 8%	642 x 228 x 281	0.028 - 0.133	9.0	graphite-grey	IP66 / IK08
111509	STATURION LED forum 2185-450	1	1 200	462	50° asym.	43 545	4 000	70	~ 8%	642 x 228 x 281	0.028 - 0.133	9.0	graphite-grey	IP66 / IK08
111510	STATURION LED forum 2196-800	2	1 050	800	8° sym.	80 964	4 000	70	≤ 3%	698 x 303 x 673	0.104 - 0.463	28.0	graphite-grey	IP66 / IK08
111511	STATURION LED forum 2192-500	2	700	514	60° sym.	61 779	4 000	70	≤ 3%	698 x 303 x 673	0.104 - 0.463	28.0	graphite-grey	IP66 / IK08
111512	STATURION LED forum 2192-800	2	1 050	800	60° sym.	82 580	4 000	70	≤ 3%	698 x 303 x 673	0.104 - 0.463	28.0	graphite-grey	IP66 / IK08
111513	STATURION LED forum 2195-800	2	1 050	800	50° asym.	79 959	4 000	70	≤ 3%	698 x 303 x 673	0.104 - 0.463	28.0	graphite-grey	IP66 / IK08
110469	STATURION LED forum 2195-900	2	1 200	914	50° asym.	88 367	4 000	70	≤ 3%	753 x 304 x 494	0.090 - 0.309	28.0	graphite-grey	IP66 / IK08
111514	STATURION LED forum 3192-1400	3	1 200	1 386	60° sym.	136 889	4 000	70	≤ 3%	757 x 303 x 673	0.104 - 0.463	30.0	graphite-grey	IP66 / IK08
103948	STATURION LED forum 3195-1400	3	1 200	1 386	50° asym.	120 487	4 000	70	≤ 3%	757 x 303 x 673	0.104 - 0.463	30.0	graphite-grey	IP66 / IK08

Further models on request

## Accessories

\* LED driver boxes for 3 module versions

Article no.	Designation
111515	DRV box forum 700mA 700W IP20
111516	DRV box forum 1200mA 1300W IP20
111517	DRV box forum 700mA 700W IP66
104127	DRV box forum 1200mA 1300W IP66